

ProLite E2271HDS-1

The ProLite E2271HDS is one of the stunning new range of LED-backlit monitors from iiyama. It is a full 1920x1080 high definition 22" monitor that features all the benefits this technology affords. Extremely slim and stylish in design, it has a narrow bezel, touch-sensitive controls and is finished in the latest glossy-black. The high specifications on the monitor include 5,000,000:1 ACR, fast 2ms response for excellent sharpness in high definition video and triple input connectivity. Power consumption is only 21W typical usage and less than 1W in standby.



Panel	LED-Backlit
Diagonal	22"
Display area h x w	268.1 x 476.6 mm
Response time	5 ms
Contrast	5 000 000 : 1 ACR
Contrast	1000 : 1 typical
Brightness	250 cd/m ² typical
Viewing zone	horizontal/vertical: 170°/160°; right/left: 85°/85°; up/down: 80°/80°
Display colour	16.7 million
Pixel pitch h x v	0.248 x 0.248 mm
Native resolution	Full HD 1080p, 1920 x 1080 (2.1 megapixel)
Horizontal sync	24 - 80 KHz
Vertical sync	55 - 75 Hz
Analog input connector	D-Sub
Digital input connector	DVI-D, HDMI
HDCP	yes
Synchronization	Separate sync
Plug & Play	VESA DDC2B™
Speakers	2 x 1 W (Stereo)
Included accessories	AC adapter, power cable, D-Sub cable, DVI-D cable, stand, screw, quick start guide, safety guide
Apple - Mac	All iiyama monitors are compatible with Apple-Macintosh computers.
Controls	Via OSD in 9 languages (EN, DE, FR, ES, IT, PT, Chinese, RU, JP) and 5 front controls (Power, Menu/Select, + /Volume, - /ECO, Auto)
User controls	luminance (brightness, contrast, ECO, picture mode, ACR), image steep (clock, phase, H. position, V. position, aspect), colour (gamma, colour temperature), OSD setup(H. position, V. position, OSD time out, language), others (reset, signal select, HDMI audio, information), volume, auto adjust
Driver	Windows 95 / 98 / 2000 / ME / XP / Vista / 7
Ergonomics	CE,VCCI-B,TUV-Bauart
Power supply	DC 12V 3A
Power Supply Unit	external
Power usage	21 W typical; max. 1 W in Power management mode
Power management	VESA DPMS, ENERGY STAR®
Anti-theft-device	Kensington-lock™ prepared
Tilt angle	12° up; 3° down
Dimensions w x h x d	525.5 x 376 x 166 mm
Weight	2.9 kg
Aspect ratio	16 : 9

All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-13406-2 in connection with pixel defects.